

Technical data
ESW[®]-Compact_II-LF_008

operating voltage	24V DC $\pm 5\%$
current input	max. 100mA
temperature range	0 to 65°C
type of protection	IP 68
case	high grade steel 1.4571/1.4404
case dimensions	94x70 mm (h x \emptyset), Fixing hole M8x1.25 ; see manual
torque	max. 30Nm, power transmission only at hexagonal bolt
weight	approx. 1,0kg (without cable), approx. 1,4kg (with cable)
sight glass	Plexiglass DIN 4102 IB2, s = 5mm
connection cable	5m, SD 90 C / Kaweflex 6430 SK-C , 7 x 0.34mm ² , with shield, cover material: PUR/PUR, min. bending radius: 50,25mm/ 53,25mm
screw-type conduit fitting	M16x1,5 Brass CuZn39Pb3, nickel-plated Lamellar insert: Polyamide PA6 V-2 Sealing ring: Polychloroprene-Nitrile rubber CR/NBR O-Ring: Nitrile rubber NBR
sensor	integrated acceleration sensor
measured value	vibration velocity in mm/s
measurement range	0 to 10 / 0 to 20 / 0 to 50mm/s, switchable
signal assessment	RMS
frequency range	1Hz to 300Hz (-3dB)
filter	Butterworth, 60dB/dec resp. 18dB/oct
analog output	0 to 20mA or 4 to 20mA current source proportional to the selected measuring range
load	max. 500Ohm
switching output	two potential free switching-contacts (30V, 1A)
switching threshold	10% to 100% of measuring range, adjustable by Potentiometer in the case
switching delay	rise time delay K1 = 5s, K2 = 2s fall time delay K1 = 0,5s
Alarm buffer	After being triggered, the alarm relay K2 remains in its alarm position until it is reset manually by an external reset.
line monitoring	In normal operation the relays are energized, the switching contacts are closed. In cause of alarm, voltage loss or cable break, the relays fall back to their rest position.
cable connection	pink +Ub yellow closer contact K1 white closer contact K2 grey analog output blue ground green middle contact K1 brown middle contact K2
optional	threaded pin M8x25mm, V4A

Technical data under reservation!

document: ESW[®]-Compact_II-LF_008-TechnDaten-englisch.doc date: 19.08.2024

ESW[®] is a registered trademark of holthausen elektronik GmbH, Wevelinghoven 38, 41334 Nettetal